

INSTALLATION INSTRUCTIONS- TP1101

Note: It is the installer/consumers responsibility to ensure:

- Product is not damaged prior to installation.
- The product has all its components.
- Water Supply Requirements:
If the pressure exceeds 550kpa, an approved pressure limiting device must be installed. If the water temperature exceeds 75°C, an approved tempering valve must be installed.
- Shower may not be suitable for use with gravity-fed water heaters.
- Failure to comply with above may avoid all warranties.

WATER SUPPLY REQUIREMENTS



Installation instructions:

<p>Step 1. Mark and drill two holes of $\phi 6\text{mm}$ for wall plugs. Then put the wall plugs into holes.</p> <p>616 - 624mm</p>	<p>Step 2. Put the base of bottom bracket in the direction shown in the picture, align the base with wall plug and tighten them with the screw.</p>	<p>Step 3. Fit hand shower holder and top bracket to sliding rail in the direction shown in the picture.</p>
<p>Step 4. Tighten the top bracket with the screw. Then fit the cover plates.</p>	<p>Step 5. Cover wall outlet with appropriate thread seal tape(not provided). Then screw elbow onto wall outlet. Ensure male thread of elbow is pointing down.</p>	<p>Step 6. Take out the hose, screw the short end of hose into the elbow, and screw the other end into the hand shower. Then place the hand shower onto the holder.</p>