UR01, WALL HUNG URINAL

Installation guide.

DESCRIPTION

The UR01 is a vitreous china wall hung urinal with back water entry and a waste trap concealed within the unit. It is designed for use with a sensor activated, timed solenoid system and is compatible with the Zenmo Smart-demand Sensor Flush Device, URSES01. See the separate instructions for the electronic component installation.

SUPPLIED WITH THE URINAL



01
Urinal UR01



02
Wall brackets and fixings



03
Flexible hose



04
PVC waste and 40mm waste pipe



05
Standard ceramic waste cover

BACK OF THE URINAL AND FITTING MEASUREMENTS



FIXING POINTS

210mm apart

INLET TO WASTE

510mm

WASTE PIPE

Ø40mm PVC

TOLERANCE

Plus or minus 5mm

ADDRESS
42 Castro Way, Derrimut VIC 3026

PHONE
(03) 8390 6300

EMAIL
sales@zenmo.com.au

WEBSITE
www.zenmo.com.au

UR01, WALL HUNG URINAL

Installation steps.

INSTALLATION STEPS

01	Inspect the urinal for any transit damage before starting installation.
02	Check the site roughing in and installation dimensions before starting. Make sure there is a stud in the wall to secure the urinal. The distance between the two fixing points is **210mm**.
03	Check and measure the water inlet, waste outlet and bracket locations to confirm the installation fit. The distance between the water inlet and the waste outlet is **510mm**.
04	Install the two mounting brackets with the screws supplied. Connect the flexible hose to the water inlet.
05	Install the PVC waste into the urinal. Connect the waste to the 40mm PVC waste pipe (supplied).
06	Fix the plastic waste trap to the wall in the correct location.
07	Mount the urinal on the brackets, making sure the water inlet and waste outlet seal correctly. Lubricant may be used. Fit the standard ceramic waste cover over the waste.
08	Test flush to check operation and for leaks. Flush the water supply piping before the operation test.
09	Apply silicone sealant around the perimeter to seal the urinal to the wall, if required.

IMPORTANT

All installations must be carried out by a licensed plumber in compliance with the Plumbing Code of Australia and any State or local government regulations.

All dimensions are in millimetres and are subject to normal manufacturing variation of plus or minus 5mm on all surfaces. As product development is ongoing, Zenmo reserves the right to vary specifications without notice.

ADDRESS
42 Castro Way, Derrimut VIC 3026

PHONE
(03) 8390 6300

EMAIL
sales@zenmo.com.au

WEBSITE
www.zenmo.com.au